

# DART SERVICE INSTRUCTION

TO AMEND INSTALLATION INSTRUCTIONS IIN-D505-1049 REV. C OR LATER APPROVED REVISION AND  
INSTRUCTIONS FOR CONTINUED AIRWORTHINESS ICA-D505-1049 REV. 1 OR LATER APPROVED REVISION

REF. TCCA STC: SH18-10  
REF. FAA STC: SR04120NY  
REF. EASA STC: 10065049

## 1.0 PURPOSE

For D505-1049-XXX Bearpaw Installations, the MS21083C4 nut requires antiseize compound to prevent galling.

## 2.0 CHANGE

Amend IIN-D505-1049 Section 3.1 and ICA-D505-1049 Sections 32.2 and 32.4 as follows (add):

Apply MIL-PRF-907 antiseize compound to NAS1802-4-32 bolts prior to installation of the MS21083C4 nuts.

## 3.0 WEIGHT AND BALANCE

This Dart Service Instruction has a negligible effect on Weight & Balance.

CANADA  
DEPARTMENT OF TRANSPORT  
AIRCRAFT CERTIFICATION  
BRANCH  
DAO # 01-O-01

APPROVED

BY:   
C. PROVENCAL (DE # 03)

DATE: 22.02.07  
CERT. NO.: SH18-10  
ISSUE NO.: 1

UNAPPROVED

A	NEW ISSUE	SAD	22.02.07
REV.	DESCRIPTION	BY	DATE
DESIGN	SAD	<b>DART AEROSPACE LTD</b> HAWKESBURY, ONTARIO, CANADA	
DRAWN	SAD		
CHECKED	MB	DRAWING NO.	REV. A2
MFG. APPR.	N/A	DSI 9876	SHEET 1 OF 1
APPROVED		TITLE	SCALE
DE APPR.		ANTISEIZE APPLICATION	NTS
DATE	22.02.07	COPYRIGHT © 2022 BY DART AEROSPACE LTD. THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.	